

PATENT APPLICATION

**SYSTEM USING MULTIPLE DISPLAY SCREENS FOR MULTIPLE
VIDEO STREAMS**

Inventor(s): Jeff Braun, a citizen of the United States of America, residing at
105 Alta Haciendas Road
Orinda, CA 94563

Assignee: MX Entertainment
660 Alabama St. 2nd Floor
San Francisco, CA 94110

Entity: Small business concern

SYSTEM USING MULTIPLE DISPLAY SCREENS FOR MULTIPLE VIDEO STREAMS

BACKGROUND OF THE INVENTION

[0001] This invention relates in general to playback of a visual production and more specifically to using multiple display screens to display multiple video streams.

[0002] Enjoyment of digital content is growing in popularity. Video and movies can be viewed from platforms such as computer systems, consumer digital devices such as video compact disc (CD), DVD players, and other displays, systems or platforms. Other formats, such as those promulgated by the Motion Picture Expert Group (MPEG) allow stored or streamed visual productions over digital networks.

[0003] Recent advances in display technology allow picture-in-picture displays of two or more video streams, or channels, on a single display device. A user, or viewer, of a television can select a primary channel and can also view other, secondary, channels in smaller windows on the single screen.

[0004] Multiple streams of video information obtained from stored media such as DVDs can also be displayed simultaneously. For example, U.S. Patent No. 6,415,101 describes a video decoding system for retrieving multiple views from a DVD content source. The views can then be selectively displayed as primary and secondary views. The secondary views are displayed within sub-windows in the primary view.

[0005] Although these approaches allow enhancement of a user's viewing experience by simultaneously presenting multiple views of video, the approaches are limited in usefulness. Therefore it is desirable to provide improvements to the prior art to enhance and expand upon content viewing for entertainment, education, efficient presentation of information and other purposes.

BRIEF SUMMARY OF THE INVENTION

[0006] A preferred embodiment of the present invention allows multiple video streams, or other image information, to be selectively directed among two or more display screens. The video streams can be directed automatically, manually or by a combination of automated and manual techniques. This allows multiple video streams to be viewed

simultaneously on different display screens to, e.g., increase the viewing area, provide selectable enhancement and control of video viewing.

[0007] In one embodiment the invention provides a method for directing two or more image streams to two or more display devices, the method comprising detecting a first video stream and associated first stream identification; detecting a second video stream and associated second stream identification; detecting a first display device and associated first display device identification; detecting a second display device and associated second display device identification; and directing the video streams to the display devices by using the identifications.

[0008] In another embodiment the invention provides a stream director for directing two or more image streams to two or more display devices, the method comprising a first input for a first video stream and associated first stream identification; a second input for a second video stream and associated second stream identification; a first output for a first display device and associated first display device identification; a second output for a second display device and associated second display device identification; and means for directing the video streams to the display devices by using the identifications.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Fig. 1 is a block diagram of a preferred embodiment of the invention; and

[0010] Fig. 2 illustrates a panoramic video feature of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0011] Fig. 1 is a diagram showing the basic approach of the invention.

[0012] In Fig. 1, image information source 102 provides content such as broadcast or pre-stored digital video data. Multiple streams are derived from the video data by retrieval hardware 104. The multiple streams are shown as "Stream 1," "Stream 2," . . . "Stream n" in Fig. 1. Naturally, any number and type of streams can be used. Different applications may use different types of streams, such as broadcast "channels," hardwired "feeds," etc. A preferred embodiment also includes auxiliary information with the streams. The auxiliary information can be included with the same carrier as the video stream information (e.g., embedded with the video signal) or it can be provided as a distinct signal, or any other suitable approach may be used. One possibility is to use standard "sub-picture" information to carry auxiliary data about an associated stream.

[0013] The stream and auxiliary data are provided to stream director 108. Stream director 108 directs the input streams among two or more display devices 130. The directed streams at 120 do not have to correspond to the arrangement or number of the input streams at 106. In other words, streams can be directed to display devices arbitrarily and dynamically. Also, it is not necessary to direct all streams. Some streams can be selectively suppressed. A single stream can be sent to multiple devices. Streams can be combined into a single display device. Other variations may be possible.

[0014] Other possible sources for auxiliary, or other, signals include control source 110 and user input device 112. Control source 110 can be an external device or an information source such as a local network, the Internet, etc. A preferred embodiment uses a typical television remote control as a user input device and can allow a user to select streams for viewing or allow directing a specific stream to a specific display device. Combinations of automated and manual (i.e., user controlled) stream direction can be used.

[0015] For example, the auxiliary information associated with a stream can describe what type of camera angle or view of a scene is contained within the stream. This allows a multi-screen "expanded" panoramic display (or "panoramic video") to be created by assigning multiple streams to their respectively positioned display devices. For example, three screens can be used in a "left," "center" and "right" arrangement as is known in the art. Then, left, center and right video streams can automatically be steered to their respective displays.

[0016] Such a panoramic video arrangement is shown in Fig. 2.

[0017] In Fig. 2, system 200 is a portion of the system 100 of Fig. 1. System 200 includes stream director 202 that can be controlled by the means discussed, above, for Fig. 1. Three streams "Stream 1," "Stream 2" and "Stream 3" are detected and, using associated auxiliary information, directed to appropriate display devices "A," "B" and "C" positioned as left, center and right displays, respectively. Display device positioning can be communicated to stream director 202 by any suitable means. For example, hardwired connectors on a physical enclosure housing stream director 202 can be pre-assigned with left, center and right display outputs. Or a user can manually configure connections for different displays. Displays and their positions can be detected automatically. Other approaches can be used.

[0018] Note that any number and position of display devices can be used. Also, display devices can be any aspect ratio or shape. Display devices can also be any suitable type such as liquid crystal display (LCD), cathode ray tube (CRT), organic light-emitting polymer (OLEP), plasma display, etc.

[0019] Stream information can come from multiple content sources. For example, data from the Internet can be used to comprise a stream. Such data can, itself, be video (e.g., MPEG-4 format), can be computer generated images, text, web page information, etc. This allows a user to specially configure a viewing environment. In a first example, a user can use three screens to view a music video. A first screen can display a specific band member of the music video, a second screen can display an overall stage view of a performance and a third screen can display a close up of a musician's hands playing an instrument. In a second example, a user can use 5 screen to view a sporting event. Three screens can be set up as left, center, right displays for panoramic video, a fourth screen can be designated to display a particular player who is recorded with a dedicated camera and video stream, and the fifth screen can display a team's performance statistics as obtained from the Internet.

[0020] Although the invention has been described with reference to specific embodiments thereof, these embodiments are merely illustrative, and not restrictive, of the invention. For example, although the invention is discussed primarily with respect to digital video, any type of image information format can be employed, including analog formats. Although a preferred embodiment contemplates obtaining streams from a DVD, any source of information can be used including any type of video player, television set (TV) set-top box (e.g., cable/TV/Satellite), etc. Various digital transmission systems, formats; encoding, encryption or compression approaches; etc., may be used with the present invention.

[0021] Any suitable programming language can be used to implement the routines of the present invention including C, C++, Java, assembly language, etc. Different programming techniques can be employed such as procedural or object oriented. The routines can execute on a single processing device or multiple processors. Although the steps, operations or computations may be presented in a specific order, this order may be changed in different embodiments. In some embodiments, multiple steps shown as sequential in this specification can be performed at the same time. The sequence of operations described herein can be interrupted, suspended, or otherwise controlled by another process, such as an operating system, kernel, etc. The routines can operate in an operating system environment or as stand-alone routines occupying all, or a substantial part, of the system processing.

[0022] In the description herein, numerous specific details are provided, such as examples of components and/or methods, to provide a thorough understanding of embodiments of the present invention. One skilled in the relevant art will recognize, however, that an embodiment of the invention can be practiced without one or more of the

specific details, or with other apparatus, systems, assemblies, methods, components, materials, parts, and/or the like. In other instances, well-known structures, materials, or operations are not specifically shown or described in detail to avoid obscuring aspects of embodiments of the present invention.

[0023] A “computer-readable medium” for purposes of embodiments of the present invention may be any medium that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, system or device. The computer readable medium can be, by way of example only but not by limitation, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, system, device, propagation medium, or computer memory.

[0024] A “processor” or “process” includes any human, hardware and/or software system, mechanism or component that processes data, signals or other information. A processor can include a system with a general-purpose central processing unit, multiple processing units, dedicated circuitry for achieving functionality, or other systems. Processing need not be limited to a geographic location, or have temporal limitations. For example, a processor can perform its functions in “real time,” “offline,” in a “batch mode,” etc. Portions of processing can be performed at different times and at different locations, by different (or the same) processing systems.

[0025] Reference throughout this specification to “one embodiment”, “an embodiment”, or “a specific embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention and not necessarily in all embodiments. Thus, respective appearances of the phrases “in one embodiment”, “in an embodiment”, or “in a specific embodiment” in various places throughout this specification are not necessarily referring to the same embodiment. Furthermore, the particular features, structures, or characteristics of any specific embodiment of the present invention may be combined in any suitable manner with one or more other embodiments. It is to be understood that other variations and modifications of the embodiments of the present invention described and illustrated herein are possible in light of the teachings herein and are to be considered as part of the spirit and scope of the present invention.

[0026] Embodiments of the invention may be implemented by using a programmed general purpose digital computer, by using application specific integrated circuits, programmable logic devices, field programmable gate arrays, optical, chemical, biological, quantum or nanoengineered systems, components and mechanisms may be used. In general,

the functions of the present invention can be achieved by any means as is known in the art. Distributed, or networked systems, components and circuits can be used. Communication, or transfer, of data may be wired, wireless, or by any other means.

[0027] It will also be appreciated that one or more of the elements depicted in the drawings/figures can also be implemented in a more separated or integrated manner, or even removed or rendered as inoperable in certain cases, as is useful in accordance with a particular application. It is also within the spirit and scope of the present invention to implement a program or code that can be stored in a machine-readable medium to permit a computer to perform any of the methods described above.

[0028] Additionally, any signal arrows in the drawings/Figures should be considered only as exemplary, and not limiting, unless otherwise specifically noted. Furthermore, the term “or” as used herein is generally intended to mean “and/or” unless otherwise indicated. Combinations of components or steps will also be considered as being noted, where terminology is foreseen as rendering the ability to separate or combine is unclear.

[0029] As used in the description herein and throughout the claims that follow, “a”, “an”, and “the” includes plural references unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise.

[0030] The foregoing description of illustrated embodiments of the present invention, including what is described in the Abstract, is not intended to be exhaustive or to limit the invention to the precise forms disclosed herein. While specific embodiments of, and examples for, the invention are described herein for illustrative purposes only, various equivalent modifications are possible within the spirit and scope of the present invention, as those skilled in the relevant art will recognize and appreciate. As indicated, these modifications may be made to the present invention in light of the foregoing description of illustrated embodiments of the present invention and are to be included within the spirit and scope of the present invention.

[0031] Thus, while the present invention has been described herein with reference to particular embodiments thereof, a latitude of modification, various changes and substitutions are intended in the foregoing disclosures, and it will be appreciated that in some instances some features of embodiments of the invention will be employed without a corresponding use of other features without departing from the scope and spirit of the invention as set forth. Therefore, many modifications may be made to adapt a particular situation or material to the essential scope and spirit of the present invention. It is intended that the invention not be

limited to the particular terms used in following claims and/or to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include any and all embodiments and equivalents falling within the scope of the appended claims.

[0032] Thus, the scope of the invention is to be determined solely by the appended claims.